TPU
Thermoplastic Polyurethane
RoHS Compliant

Polyurethane Tubing

Transparent Ether Formula

- Hardness, Shore A 85
- UV stable - good for outdoor use
- Excellent resistance to weathering and fungus
- Resin material certified to NSF 61
- Max operating temperature 175 °F
- Resistance to, impact, abrasion and repeated flexing
- Exhibits excellent hydrolytic stability and low temperature properties

Tube Number	ID	OD	Wall Thickness	*Standard Roll*
TPU 1-2 N	1/16"	1/8"	1/32"	100 ft.
TPU 2-3 N	1/8"	3/16"	1/32"	100 ft.
TPU 2-4 N	1/8"	1/4"	1/16"	100 ft.
TPU 3-5 N	3/16"	5/16"	1/16"	100 ft.
TPU 4-6 N	1/4"	3/8"	1/16"	100 ft.
TPU 5-7 N	5/16"	7/16"	1/16"	100 ft.
TPU 6-8 N	3/8"	1/2"	1/16"	100 ft.
TPU 8-10 N	1/2"	5/8"	1/16"	100 ft.
TPU 8-12 N	1/2"	3/4"	1/8"	100 ft.
TPU 10-14 N	5/8"	7/8"	1/8"	100 ft.
TPU 12-16 N	3/4"	1"	1/8"	100 ft.
TPU 16-20 N	1"	1 1/4"	1/8"	100 ft.

Operating Temp: to 80 °C (175 °F) • Shore A 85 hardness FDA 21 CFR 177.2600 - food contact

TPU Colors
RoHS Compliant

NEW

- Excellent material for thermoformed tubes
- Available in sizes listed above - 2000' minimum order
- Same material as transparent ether formula above

See Rotating Lock Luers - page 10 and CryatalVu™ Swivel Disconnects - page 14 for color-matched connectors.

Rose
Yellow
Orange
Lime
Berry
Violet

- Hardness, Shore A 85
- UV stable - good for outdoor use
- Max operating temperature 175 °F
- Max operating temperature 80 °C

Eldon James

Ph. 970.667.2728 • eldonjames.com • fax 970.667.3204